

\$	\$\$	\$\$\$	\$\$\$\$
----	------	--------	----------

15mm (9/16") Exposed Tee System

Key Selection Attributes

- Hot dipped galvanized coating inhibits red rusting better than electrogalvanized, painted or tin plated systems
- System is engineered and designed to fit and provide a finish to coordinate with Armstrong Ceilings
- 10-year limited warranty; 15-year with HumiGuard™ Plus products

PeakForm Main Beam Key Attributes:

- Peakform patented main beam profile for installation with Suprafine XL stab-end cross tees

- The Peakform bulb design increases strength and stability for improved performance
- Superlock main beam clip engineered for a strong, secure connection and fast accurate alignment confirmed with an audible click
- Easy to cut thanks to the Peakform bulb design
- Rotary stitched for additional torsional strength and extra stability during installation
- Slots at 100mm centres for more flexibility (3600mm long main beam)
- Easy to remove and relocate
- Faster easier insertion/installation of XL cross tees
- Tighter tee to tee connection
- It has better load carrying capability
- Armstrong Global White

Typical Applications

- Offices
- School
- Hospitality
- Retail
- Healthcare



Visual Selection

Performance Selection

GRID FACE	ITEM NUMBER	DESCRIPTION	DIMENSIONS	Load (kg/m)	ASTM/DUTY CLASS
SUPRAFINE Main Beams					
15mm 9/16"	BP754042 BP754942	3600mm Main Beam 12'	3600x15x43mm 144X9/16"X1-11/16"	19.76	ID
15mm 9/16"	BP7542102 BP7547102	3000mm Main Beam 10'	3000x15x32mm 120X9/16"X1-1/4"	—	LD
SUPRAFINE XL Cross Tee					
15mm 9/16"	BP753042 BP753742	1200mm Cross Tee 4'	1200x15x43mm 48X9/16"X1-11/16"	—	—
15mm 9/16"	BP7530102 BP7537102	1200mm Cross Tee 4'	1200x15x32mm 48X9/16"X1-1/4"	—	—
15mm 9/16"	BP753061 BP753761	1200mm Cross Tee 4'	1200x15x27mm 48X9/16"X1-1/16"	—	—
15mm 9/16"	BP752042 BP752742	600mm Cross Tee 2'	600x15x43mm 24X9/16"X1-11/16"	—	—
15mm 9/16"	BP752061 BP752761	600mm Cross Tee 2'	600x15x27mm 24X9/16"X1-1/16"	—	—
15mm 9/16"	BP7520102 BP7527102	600mm Cross Tee 2'	600x15x32mm 24X9/16"X1-1/4"	—	—
Molding					
19mm	BPT1945H	3000mm Angle Molding	3600x19x19mm	—	—
14mm	BP784003	3600mm Shadow Molding	3600X19X7X14mm	—	—

ASTM Class
 HD - Heavy-duty
 ID - Intermediate-duty
 LD - Light-duty

Details

